

130ZYT PMDC Motors

Magnet (磁铁): Ferrite 铁氧体
 Insulation Class 绝缘等级: B, F
 Protection 防护等级: IP54
 Shaft OD 出轴直径: 10~19mm
 Winding 绕线选择: Ball



1. Voltage 工作电压范围: 12~ 220VDC
2. Speed 额定转速范围: 750 ~3,000 RPM
3. Power 输出功率范围: 300 ~1000 W

● **Motor Specifications (马达特性)**

Model	Rated Voltage	No Load		Rated(额定)						Motor Length
		Speed	Current	Speed	Current	Torque		Power	Eff.	
	Vdc	RPM	Amp	RPM	Amp	oz-in	mNm	W	%	mm
130ZYT230-24-28	24	2800	12	2500	48	433.2	3059	801	69.5	230
130ZYT230-110-17	110	1700	1.5	1500	7.2	541.5	3824	601	75.8	230
130ZYT230-220-7	220	700	0.5	600	1.8	676.2	4775	300	75.8	230
130ZYT278-24-22	24	2200	10	1950	42	521.1	3680	751	74.6	278
130ZYT278-220-17	220	1700	1	1500	4.5	676.2	4775	750	75.8	278

● **Motor Dimensions (外形尺寸图)**

